

MIDIBOX Series

Prefabricated lifting station for clean and gray water in compliance with EN 12050-2 standard.

Specifications

The station is equipped with:

- Polyethylene basin with a capacity of 110 litres, equipped with a threaded cover.
- Cable glands for power supply cables (and floats).
- Rp 1"1/4 or 1"1/2 delivery pipes with fast connection and ring nut for easy disassembly of the pump.
- 3 fast connections:
 - 1 x DN110 for inlet,
 - 1 x DN50 for ventilation and
 - 1 x DN65 for cable connection.
- 1 x DN50 fast connection for the manual pump.
- DOC or DOMO 7 submersible pump, vortex or channel impeller type.
- QDR control panel for threephase versions.

Midibox can be installed on the floor or buried in a suitable structure following instructions in the "Instructions and Operative Manual".

Easy installation:

- installation is quick and easy: for the single-phase versions you just connect the pipes and the electrical cables; for the three-phase versions you also need to connect the control panel.
- The new Midibox is provided with side handles for ease of handling.
- Pre-installed delivery pump and unions.

Ecological solution:

- tank made from 100% recyclable polyethylene.

Easy maintenance and repair.

- Tried and tested pump technology.
- Pump quick and easy to remove thanks to the ring nut located

Accessories

Ball check valves

Alarm kit

Connector kit

Manual pump



For a complete list of technical information, consult www.lowara.com